

WORKLIGHTS



**20V MAX* Tool Connect™
Cordless/Cordless
LED Area Light Kit**



**20V MAX* Tool Connect™
Cordless/Cordless
LED Area Light**



**18V/20V MAX*
Cordless/Cordless LED
Worklight (Tool Only)**



**18V/20V MAX*
LED Worklight
(Tool Only)**



**20V MAX*
LED Worklight
(Tool Only)**

SPECIFICATIONS	DCL070T1	DCL070	DCL061	DCL060	DCL050
Volts	20V MAX*	20V MAX*	18V or 20V MAX* or AC/DC Power	18V or 20V MAX*	20V MAX*
Bulb	LED	LED	LED	LED	LED
Brightness	Up to 7,000 lumens	Up to 7,000 lumens	1500 lumens	1500 lumens	500 & 250 lumens
Run-Time	-	-	Up to 2.5 hrs	Up to 2.5 hrs	Up to 17 hrs.
Weight	29.3 lbs	27 lbs	3.27 lbs	3.27 lbs	2 lbs
Charger/Batteries	Charger / (1) 20V/60V MAX* Lithium Ion (6.0 Ah)	Sold Separately	Sold Separately	Sold Separately	Sold Separately



**20V MAX* LED
Hand Held Worklight**



**20V MAX* Jobsite LED
Spotlight (Tool Only)**



**20V MAX* LED
Worklight (Tool Only)**



**18V Flexible
Floodlight (Tool Only)**



**18V Fluorescent
Area Light (Tool Only)**

SPECIFICATIONS	DCL044	DCL043	DCL040	DW919	DC527
Volts / Power Source	20V MAX*	20V MAX*	20V MAX*	18V	18V
Bulb	LED	LED	LED	Bulb	Fluorescent
Brightness	160 lumens	1000 & 90 lumens	110 lumens	-	-
Run-Time	Up to 27 hrs	Up to 13.5 hrs	Up to 11 hrs	Up to 3 hrs	Up to 3.5 hrs
Weight	1.5 lbs	1.4 lbs (tool only)	1.0 lbs (tool only)	0.5 lbs (tool only)	1.2 lbs (tool only)
Charger/Batteries	Sold Separately	Sold Separately	Sold Separately	Sold Separately	Sold Separately



**14.4V Pivoting Head
Flashlight (Tool Only)**



**12V MAX* LED Worklight
(Tool Only)**



**8V MAX* Worklight
(Tool Only)**



**LED Replacement
Bulb**

SPECIFICATIONS	DW906	DCL510	DCL023	DCL0900
Volts / Power Source	14.4V	12V MAX*	8V MAX*	9.6V - 36V
Bulb	Xenon bulb	LED	LED	LED
Brightness	-	130 lumens	80 lumens	110 lumens
Run-Time	Up to 3 hrs	Up to 4 hrs	Up to 5 hrs.	Up to 4 hrs
Weight	0.5 lbs (tool only)	0.5 lbs (tool only)	0.6 lbs (tool only)	0.2 lbs (tool only)
Charger/Batteries	Sold Separately	Sold Separately	Sold Separately	-



12V MAX* Infrared Thermometer Kit



12V MAX* Imaging Thermometer Kit

SPECIFICATIONS	DCT414S1	DCT416S1
Volts	12V MAX*	12V MAX*
Temperature Range	-20° F to 932° F (-29° C to 500° C)	14° F to 480° F (-10° C to 250° C)
Field of View; Distance, Spot	(D:S) 12:1	(IFOV) 1" @ 39.3" (25 mm @ 1m)
Accuracy	+/-1.5% or +/- 1.5° C, whichever is greater, assumes ambient operating temperature	Below 200° F, +/-3.6° F, Above 200° F, +/-2%, assumes ambient operating temperature
Charger/Batteries	Charger / (1) 12V MAX* Lithium Ion	Charger / (1) 12V MAX* Lithium Ion
Includes	-	Micro SD card, Report writing software



**12V MAX* (17 mm) Inspection Camera
with Wireless Screen Kit**



**12V MAX* (9 mm) Inspection Camera
with Wireless Screen Kit**



**12V MAX* (5.8 mm) Inspection Camera
with Wireless Screen Kit**

SPECIFICATIONS	DCT410S1	DCT411S1	DCT412S1
Volts	12V MAX*	12V MAX*	12V MAX*
Camera Head Diameter	17 mm	9 mm	5.8 mm
Cable Length	3' waterproof	3' waterproof	3' waterproof
Screen Size	3.5"	3.5"	3.5"
Resolution	320x480 dpi	320x480 dpi	320x480 dpi
Zoom	3X	3X	3X
Charger/Batteries	Charger / (1) 12V MAX* Lithium Ion	Charger / (1) 12V MAX* Lithium Ion	Charger / (1) 12V MAX* Lithium Ion
Includes	17 mm - 3' camera cable, hook, & magnet	9 mm - 3' camera cable, hook, magnet, & mirror	5.8 mm - 3' camera cable

